



FEATURES & BENEFITS

- Designed to meet the requirements of EN54-3
- Provides high reliability and error detection
- Short circuit isolators in each device
- Large capacity, up to 240 devices per loop
- Addressable via VPU100 programmer
- Auto addressing capability (Control panel feature)
- OEM password protection
- High power availability from loop (>98%),
- Digital checking of double address
- Line quality information

SPECIFICATION

Vega loop powered platform sounder designed around a fully digital protocol.

Fixing platform for VEGA detector base.

The device offers wide-angle and uniform sound distribution providing good audibility in all directions.

Synchronized start.

Low current consumption 90 db sounder.

Compact design

Suitable for multistage alarm application.

TECHNICAL SPECIFICATIONS	
Power Supply	15-40 V
Current Consumption	I=4 mA
Operating Temperature Range	-10°C / +55°C
Sound output	90 dB
Alarm Tones (5)	(3)Intermittent 990Hz at 1Hz (500ms ON / 500ms OFF) (4)Slow whoop 500Hz to 1200Hz (3.5s sweep, 0.5s silence then repeat) (5)Sweep1200Hz to 500Hz at 1Hz (DIN tone)
(1)Alternating 990 & 650Hz at 2Hz (250ms 250ms) (2)Continuous 990Hz	
Colors	White
Weight	160 gm