

Wireless Remote Indicator

The Wireless Taurus Remote Indicator is a programmable output device which can be operated by the control panel in the event of fire, alarm or fault conditions from selected devices.

The activation command is sent from the control panel to the indicator through the wireless translator module.

Bi-directional communications with the wireless translator is based on a proven protocol and wireless technology and is fast, reliable and provides the highest level of security.



Features

- Bi-directional wireless communication
- Can be used with Taurus addressable and conventional translators
- 22 pairs of field channels
- Dual channel redundancy
- Long communication range ($\cong 1$ km in open air)
- 5 year battery life
- Utilises standard low cost lithium battery technology
- Rapid, cost effective installation with minimal disturbance
- Easy scan & link programming option
- 5 year product warranty

Specification

Operating frequency range	868 MHz
Max radiated power	14 dBm (25 mW)
Batteries	2 x CR123A (3 V & 1.2 Ah)
Batteries lifespan	5 years
Operating temperature	-10°C - +55°C
Max tolerated humidity (no condensing)	95% RH
Dimensions H x W x D mm	80 x 80 x 32
Weight (without batteries)	60 gr

Order Codes and Options

TW-RI-01	Wireless Remote Indicator
----------	---------------------------

[Check if this document is up to date](#)

Argus Security Srl, Via del Canneto, 14, 34015 Muggia, (TS), Italia **T:** +39-040.23.96.411, **E:** info@argussecurity.it, **W:** www.argussecurity.it

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.